NSN 5895-00-692-2912

Pulse Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-692-2912

Inclosure Material:
Aluminum
Overall Length:
22.500 inches
Overall Height:
8.750 inches
Overall Width:
19.000 inches
Average Life Measurement:
Not rated
End Application:
An/mps-7; an/fps-20 radar control group
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Installation Design:
Drawer
Circuit Construction Type:
Solid state
Impedance Rating Per Channel:
50.000 ohms output channel
Polarity Per Channel:
Positive output channel
Pulse Repetition Rate Per Channel:
123.800 pulses per second operating channel
Pulse Peak Amplitude Per Channel:
35.000 volts 1st output channel err-100
Signal Data Type Per Channel:
Output channel pulse
Output Wave Shape:
Square
Operating Ac Frequency In Hertz:
60.0 single voltage
External Ac Operating Voltage In Volts:
120.0 single voltage
Phase:
Single
Functional Description:
Kgenerates pulses for measurement of range on ppi indicator and contains provisions for internally calibrating range markers; also contains
generator for azimuth markers for ppi and a self-contained power supply

Reference Data And Literature:

Fig 168-1, t.O. 31p6-2fps20.4, technical manual, illustrated parts breakdown, radar sets an/fps-20, pg 434

NSN 5895-00-692-2912

Pulse Generator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200