NSN 5895-00-726-3169

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-726-3169

Overall Length:
2.469 inches
Overall Height:
1.375 inches
Overall Width:
2.375 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
50.0
Operating Tempurature Range:
+0.0 to 60.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Irregular
Identification Designator:
2531k-07180
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Open
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
300.0 megahertz output channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms input channel
Maximum Continuous Operating Time In Hours: Not rated
Shock Pulse Duration Time:
11.0 milliseconds

NSN 5895-00-726-3169

Frequency Mixer Stage - Page 2 of 2



Connection Type And Location:

Solder lug rear

Connection Contact Type And Quantity:

2 solder lug external

Special Features:

Vswr 1.5 max

Fsc Application Data:

Radar equipment, except a1rborne

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200