

View Online at <https://aerobasegroup.com/nsn/5895-00-777-3431>

**Case Material:**

Aluminum alloy, qq-a-250/8, alloy 5052, h32

**Case Surface Treatment:**

Painted

**Connector Manufacturer Code:**

96906 and 96906 and 96906 and 96906

**Connector Manufacturer Part Number:**

Ms3106r36-9s and ms3106r20-4s and ms3100r28-11pw and ms3100r28-11p

**Maximum Voltage Rating In Volts:**

220.0 ac

**Inclosure Type:**

Partially enclosed

**Terminal Location:**

Back

**Power Source:**

External

**Mounting Method:**

Flush panel

**Terminal Type And Quantity:**

2 connector plug and 2 connector, receptacle

**Maximumlength:**

21.940 inches

**Maximumwidth:**

8.380 inches

**Maximumheight:**

7.700 inches

**Intelligence Data Handling Capability:**

Electrical frequency receiving automatic and time/hours receiving automatic and electrical current receiving automatic and power source transmitting manual

**Indication Method:**

Receiving vibrating reed and receiving meter movement and receiving dial

**Phase:**

Three

**Special Features:**

Mil-std-171, finish no. 21.11, olive drab color no. X24087

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A31700

**Mil-std (military Standard):**

Mil-std-171 spec.