

View Online at <https://aerobasegroup.com/nsn/5895-00-777-3431>

Case Material:

Aluminum alloy, qq-a-250/8, alloy 5052, h32

Case Surface Treatment:

Painted

Connector Manufacturer Code:

96906 and 96906 and 96906 and 96906

Connector Manufacturer Part Number:

Ms3106r36-9s and ms3106r20-4s and ms3100r28-11pw and ms3100r28-11p

Maximum Voltage Rating In Volts:

220.0 ac

Inclosure Type:

Partially enclosed

Terminal Location:

Back

Power Source:

External

Mounting Method:

Flush panel

Terminal Type And Quantity:

2 connector plug and 2 connector, receptacle

Maximumlength:

21.940 inches

Maximumwidth:

8.380 inches

Maximumheight:

7.700 inches

Intelligence Data Handling Capability:

Electrical frequency receiving automatic and time/hours receiving automatic and electrical current receiving automatic and power source transmitting manual

Indication Method:

Receiving vibrating reed and receiving meter movement and receiving dial

Phase:

Three

Special Features:

Mil-std-171, finish no. 21.11, olive drab color no. X24087

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A31700

Mil-std (military Standard):

Mil-std-171 spec.