NSN 5895-00-825-5325

Multiplexer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5895-00-825-5325

Overall Length:
4.688 inches
Overall Height:
1.281 inches
Overall Width:
4.500 inches
Ac Voltage Rating:
6.3 volts
Dc Voltage Rating:
300.0 volts
Frequency Rating:
400.0 hertz
Internal Battery Accommodation:
Not included
Input Impedance Rating:
300.0 kilohms
Output Impedance Rating:
2.0 kilohms
Multiplexing Method:
Time division
Channel Type And Quantity:
Channel Type And Quantity: 2 receiving
2 receiving
2 receiving Input Frequency Bandwidth:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase: Single
Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase: Single Shelf Life:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase: Single Shelf Life: N/a
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase: Single Shelf Life: N/a
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase: Single Shelf Life: N/a Unit Of Measure:
2 receiving Input Frequency Bandwidth: 100.0 kilohertz Input Frequency Rating: Between 0.0 hertz and 800.0 hertz Output Frequency Bandwidth: 100.0 kilohertz Output Frequency Rating: Between 380.0 hertz and 420.0 hertz Phase: Single Shelf Life: N/a Unit Of Measure: Demilitarization: