NSN 5895-00-973-3595

Frequency Mixer Stage - Page 1 of 2



, , , , ,
View Online at https://aerobasegroup.com/nsn/5895-00-973-3595
Overall Length:
2.435 inches
Overall Height:
2.435 inches
Overall Width:
1.485 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
Not rated
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
Sm-d-44744-49671
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
53.0 megahertz 2nd input channel err-100
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated

Not rated

Connection Type And Location:

Maximum Continuous Operating Time In Hours:

Impedance Rating Per Channel: 60.000 ohms input channel err-100

Printed circuit bottom

NSN 5895-00-973-3595

Frequency Mixer Stage - Page 2 of 2



Connection	Contact	Type And	Quantity:
COMMECTION	Contact	I ype Allu	Qualitity.

6 printed circuit external

External Dc Operating Voltage In Volts:

10.0 single voltage

Test Data Document:

80063-csca4-01768 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Fsc Application Data:

Radio, except navigation, nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200