NSN 5895-00-996-5812

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-996-5812

Overall Length:
4.000 inches
Overall Height:
0.062 inches
Overall Width:
4.000 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
Not rated
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Open
Operating Control Method:
Manual
Installation Design:
Panel
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
0.9 megahertz input channel err-100
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms input channel err-100
Maximum Continuous Operating Time In Hours:
Not rated
INUL TALEU

NSN 5895-00-996-5812

Frequency Mixer Stage - Page 2 of 2



External Dc Operating Voltage In Volts:

20.0 single voltage

Fsc Application Data:

Miscellaneous communications equipment non-airborne

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200