NSN 5895-01-013-6507

Electronic Frequency Converter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-013-6507

| Overall Length: | | | | |
|---|--|--|--|--|
| Between 2.990 inches and 3.010 inches | | | | |
| Overall Height: | | | | |
| 1.145 inches | | | | |
| Overall Width: | | | | |
| 0.620 inches | | | | |
| Vibration Resistance Range In Hertz: | | | | |
| Not rated | | | | |
| Individual Section Quantity: | | | | |
| 1 | | | | |
| Shock Resistance Rating In Gravitational Units: | | | | |
| Not rated | | | | |
| Operating Tempurature Range: | | | | |
| +0.0/+65.0 degrees celsius | | | | |
| Average Life Measurement: | | | | |
| Not rated | | | | |
| Basic Shape Style: | | | | |
| Rectangular or square | | | | |
| Identification Designator: | | | | |
| 77c712631-03538 | | | | |
| Maximum Operating Altitude Rating: | | | | |
| Not rated | | | | |
| Inclosure Type: | | | | |
| Hermetically sealed | | | | |
| Installation Design: | | | | |
| Mechanical | | | | |
| Circuit Construction Type: | | | | |
| Solid state | | | | |
| Frequency Per Channel: | | | | |
| 3650.0 megahertz 2nd output channel err-100 | | | | |
| Attenuation In Decibels: | | | | |
| Not rated | | | | |
| Average Power Rating Per Channel: | | | | |
| 50.0 milliwatts input | | | | |
| Signal Voltage Rating Per Channel: | | | | |
| Not rated | | | | |
| Overall Gain: | | | | |
| Not rated | | | | |
| Impedance Rating Per Channel: | | | | |
| 50.000 ohms operating channel | | | | |
| Maximum Continuous Operating Time In Hours: | | | | |

Not rated

NSN 5895-01-013-6507

Electronic Frequency Converter - Page 2 of 2



| Connection | Type | And | Location: |
|------------|------|-----|-----------|
|------------|------|-----|-----------|

Receptacle, coaxial bottom

Connection Contact Type And Quantity:

3 receptacle, coaxial external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200