NSN 5895-01-020-3566

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-020-3566

Overall Length:

Between 1.940 inches and 1.970 inches

Overall Height:

Between 0.580 inches and 0.620 inches

Overall Width:

Between 1.420 inches and 1.460 inches

Environmental Protection:

Vibration and shock resistant

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Vibration Resistance Amplitude:

0.06 inches total excursion

Shock Resistance Rating In Gravitational Units:

50.0

Operating Tempurature Range:

-54.0/+100.0 degrees celsius

Average Life Rating:

1000.0

Average Life Measurement:

Hours

Average Life Rating In Hours:

1000.0

Basic Shape Style:

Rectangular or square

Identification Designator:

6900-27-600-1007

Maximum Operating Altitude Rating:

75000.0 feet

Inclosure Type:

Encased

Installation Design:

Mechanical

Circuit Construction Type:

Solid state

Frequency Per Channel:

3.0 megahertz operating channel err-100

Attenuation In Decibels:

7.5

Average Power Rating Per Channel:

50.0 milliwatts input

Signal Voltage Rating Per Channel:

Not rated

NSN 5895-01-020-3566

Frequency Mixer Stage - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Receptacle, coaxial front
Connection Contact Type And Quantity:
3 receptacle, coaxial internal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32200