NSN 5895-01-023-7893

Overall Length:

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-023-7893

0.910 inches	
Overall Height:	
0.500 inches	
Overall Width:	
0.590 inches	
Environmental Protection:	
Shock resistant and vibration	
Vibration Resistance Range In Hertz:	
+10.0/+2000.0	
Vibration Resistance Amplitude:	
0.06 inches total excursion	
Shock Resistance Rating In Gravitational Uni	ts:
50.0	
Operating Tempurature Range:	
-55.0/+110.0 degrees celsius	
Average Life Rating:	
1000.0	
Average Life Measurement:	
Hours	
Average Life Rating In Hours:	
1000.0	
Basic Shape Style:	
Rectangular or square	
Identification Designator:	
6900-20-600-1007	
Maximum Operating Altitude Rating:	
75000.0 feet	
Inclosure Type:	
Encased	
Installation Design:	
Module	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
500.0 megahertz operating channel err-100	
Attenuation In Decibels:	
9.0	
Average Power Rating Per Channel:	
100.0 milliwatts output	
Signal Voltage Rating Per Channel:	

Not rated

NSN 5895-01-023-7893

Frequency Mixer Stage - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Wire lead terminals bottom
Connection Contact Type And Quantity:
6 wire lead terminals external
Special Features:
Color bead around terminal no. 1 signifying rf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A32200