NSN 5895-01-032-7920



Frequency Mixer Stage - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5895-01-032-7920 **Overall Length:** 0.780 inches **Overall Height:** 0.368 inches **Overall Width:** 0.400 inches **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -54.0/+100.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Building block 25a **Basic Shape Style:** Rectangular or square **Identification Designator:** 210-769-00-33399 **Maximum Operating Altitude Rating:** 656000.0 feet **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 500.0 megahertz operating channel err-100 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** Not rated **Overall Gain:** Not rated

Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
Not rated

NSN 5895-01-032-7920

Frequency Mixer Stage - Page 2 of 2



	C	onne	ction	Type	And	Location
--	---	------	-------	-------------	-----	----------

Solder lug bottom

Connection Contact Type And Quantity:

7 solder lug external

External Dc Operating Voltage In Volts:

15.0 single voltage

Fsc Application Data:

Miscellaneous communication equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200