NSN 5895-01-062-8803

Reference Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-062-8803 **Overall Length:** 13.000 inches **Overall Height:** 4.250 inches **Overall Width:** 7.000 inches **Environmental Protection:** Moisture proof **Vibration Resistance Range In Hertz:** +5.0/+15.0 and +16.0/+25.0 and +26.0/+33.0 **Vibration Resistance Amplitude:** 3.5 gravitational units and 6.5 gravitational units and 5.5 gravitational units **Shock Resistance Rating In Gravitational Units:** 60.0 **Operating Tempurature Range:** +0.0/+75.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 20-1236665-1-07397 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Installation Design:** Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 3.0 gigahertz operating channel err-100 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: Not rated **Overall Gain:** Not rated Impedance Rating Per Channel:

50.000 ohms operating channel

NSN 5895-01-062-8803

Reference Signal Generator - Page 2 of 2



Pulse Peak Amplitude Per Channel:
Not rated
Signal Data Type Per Channel:
Operating channel radio frequency
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
20.0 milliseconds
Connection Type And Location:
Receptacle, coaxial front and receptacle, power front
Connection Contact Type And Quantity:
11 receptacle, coaxial internal and 9 receptacle, power external
External Dc Operating Voltage In Volts:
24.0 2nd voltage err-100
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32200