

View Online at <https://aerobasegroup.com/nsn/5895-01-076-7063>

Overall Length:

3.100 inches

Overall Diameter:

2.120 inches

Environmental Protection:

Dustproof and fungus proof and moisture proof and vibration

Vibration Resistance Range In Hertz:

+55.0/+200.0

Individual Section Quantity:

1

Vibration Resistance Amplitude:

40.0 gravitational units

Operating Temperature Range:

-25.0/+150.0 degrees fahrenheit

Average Life Measurement:

Not rated

Basic Shape Style:

Cylindrical

Identification Designator:

Sm-a-916470-80063

Maximum Operating Altitude Rating:

10000.0 feet

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

8.4 gigahertz input channel err-100

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

10.0 milliwatts input

Signal Voltage Rating Per Channel:

15.000 volts input

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms input channel

Indicator Device Type And Quantity:

1 meter

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

6.0 microseconds

Connection Type And Location:

Receptacle, coaxial right side and receptacle, power left side

Connection Contact Type And Quantity:

1 receptacle, coaxial internal and 1 receptacle, power external

External Dc Operating Voltage In Volts:

15.0 single voltage

Special Features:

Monitor output provides analog signal driving meter giving linear function of rf input power

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200