NSN 5895-01-078-2272

Frequency Divider - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-078-2272

Overall Length:
1.010 inches
Overall Height:
1.010 inches
Overall Width:
0.225 inches
Vibration Resistance Range In Hertz:
+20.0/+2000.0
Vibration Resistance Amplitude:
20.0 gravitational units
Shock Resistance Rating In Gravitational Units:
20.0
Operating Tempurature Range:
-32.0/+85.0 degrees celsius
Average Life Measurement:
Hours
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Free-standing
Control Type:
Local
Circuit Construction Type:
Solid state
Switching Rate Per Second:
4000
Frequency Per Channel:
500.0 megahertz operating channel
Frequency Adjustment Type:
Continuous
Signal Voltage Rating Per Channel:
66.000 volts output
Impedance Rating Per Channel:
1.000 ohms operating channel
Connection Type And Location:
Wire lead terminals left side and wire lead terminals right side
Connection Contact Type And Quantity:
Curing lead to main all automal

6 wire lead terminals external

NSN 5895-01-078-2272

Frequency Divider - Page 2 of 2



Evtornal	DcO	nerating	Voltage	In Valte	
⊑xternai	טטט	beraunu	voitage	III VOILS	

6.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200