Reference Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-082-2930

Overall Length:
12.000 inches
Overall Height:
4.960 inches
Overall Width:
8.350 inches
Environmental Protection:
Moisture proof
Vibration Resistance Range In Hertz:
+5.0/+15.0 and +16.0/+25.0 and +26.0/+33.0
Vibration Resistance Amplitude:
3.5 gravitational units and 6.5 gravitational units and 5.5 gravitational units
Shock Resistance Rating In Gravitational Units:
60.0
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
20-1236665-3-07397
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
21.0 gigahertz operating channel err-100
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms operating channel

## NSN 5895-01-082-2930

Reference Signal Generator - Page 2 of 2



**Pulse Peak Amplitude Per Channel:** Not rated Signal Data Type Per Channel: Operating channel radio frequency Maximum Continuous Operating Time In Hours: Not rated **Shock Pulse Duration Time:** 20.0 milliseconds **Connection Type And Location:** Receptacle, coaxial front and receptacle, power front **Connection Contact Type And Quantity:** 8 receptacle, coaxial internal and 9 receptacle, power external **External Dc Operating Voltage In Volts:** 24.0 2nd voltage err-100 Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli Fiig: A32200