

View Online at <https://aerobasegroup.com/nsn/5895-01-087-9493>

Overall Length:

2.390 inches

Overall Height:

1.580 inches

Overall Width:

0.565 inches

Environmental Protection:

Weatherproof and dustproof and vibration and shock resistant and raintight and dust tight and fungus proof and salt spray resistant

Vibration Resistance Range In Hertz:

Not rated

Individual Section Quantity:

3

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

-50.0/+125.0 degrees fahrenheit

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

803412-1-96214

Maximum Operating Altitude Rating:

10000.0 feet

Inclosure Type:

Encapsulated

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

4.2 gigahertz 1st input channel err-100

Frequency Adjustment Type:

Continuous

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Indicator Device Type And Quantity:

1 cathode ray tube

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, coaxial bottom

Connection Contact Type And Quantity:

1 receptacle, coaxial external

Special Features:

3 sma female coaxial type connector

Test Data Document:

96906-mil-std-210 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200