# NSN 5895-01-099-4041

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-099-4041

| Overall Length:   |
|---|
| 0.750 inches  |
| Overall Height:   |
| 0.208 inches  |
| Overall Width:  |
| 0.385 inches  |
| Environmental Protection:   |
| Moisture proof and salt spray resistant                               |
| Vibration Resistance Range In Hertz:                                  |
| +10.0/+200.0  |
| Shock Resistance Rating In Gravitational Units:                       |
| 10.0  |
| Operating Tempurature Range:  |
| -18.0/+85.0 degrees celsius   |
| Average Life Rating:  |
| 10000.0   |
| Average Life Measurement:   |
| Hours   |
| Average Life Rating In Hours:   |
| 10000.0   |
| Basic Shape Style:  |
| Rectangular or square   |
| Identification Designator:  |
| 979124-49956  |
| Maximum Operating Altitude Rating:                                    |
| 10000.0 feet  |
| Inclosure Type:   |
| Hermetically sealed   |
| Operating Control Method:   |
| Automatic   |
| Installation Design:  |
| Module  |
| Control Type:   |
| Remote  |
| Circuit Construction Type:  |
| Solid state   |
| Frequency Per Channel:  |
| 1.0 megahertz operating channel and 500.0 megahertz operating channel |
| Impedance Rating Per Channel:   |
| 50.000 ohms operating channel   |
| Maximum Continuous Operating Time In Hours:                           |
| Not rated   |
|   |

# NSN 5895-01-099-4041

Frequency Mixer Stage - Page 2 of 2



**Connection Type And Location:** 

Solder lug bottom

#### **Connection Contact Type And Quantity:**

8 solder lug external

Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A32200