

View Online at <https://aerobasegroup.com/nsn/5895-01-101-5782>

Overall Length:

Between 2.940 inches and 3.050 inches

Overall Height:

Between 0.580 inches and 0.620 inches

Overall Width:

Between 0.660 inches and 0.735 inches

Surface Luster:

Matte

Vibration Resistance Range In Hertz:

+50.0/+2000.0

Individual Section Quantity:

1

Vibration Resistance Amplitude:

24.06 gravitational units

Operating Temperature Range:

-54.0/+100.0 degrees celsius

Storage Temperature Range:

-65.0/+100.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

Receiving set, countermeasures an/wlq- (v)

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

2.5 gigahertz 1st input channel err-100 and 2.95 gigahertz 1st input channel err-1003.5 gigahertz 1st input channel err-100 and 4.0 gigahertz 1st input channel err-1003.0 gigahertz 2nd input channel err-10050.0 megahertz output channel err-100 and 500.0 megahertz output channel err-100500.0 megahertz output channel err-100 and 1000.0 megahertz output channel err-100

Connection Type And Location:

Receptacle, coaxial front

Connection Contact Type And Quantity:

3 receptacle, coaxial external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200