

View Online at <https://aerobasegroup.com/nsn/5895-01-101-6264>

Inclosure Material:

Aluminum

Overall Length:

0.830 inches

Overall Height:

0.540 inches

Overall Width:

0.830 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+5.0/+15.0 and +16.0/+25.0

Individual Section Quantity:

1

Vibration Resistance Amplitude:

2.0 gravitational units and 2.5 gravitational units

Shock Resistance Rating In Gravitational Units:

50.0

Operating Temperature Range:

+0.0/+85.0 degrees celsius

Storage Temperature Range:

-62.0/+71.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

Receiving set, countermeasures an/wlq- (v)

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

2.0 gigahertz output channel err-100 and 4.0 gigahertz output channel err-100

Shock Pulse Duration Time:

10.0 milliseconds

Connection Type And Location:

Receptacle, coaxial front and receptacle, coaxial left side and receptacle, coaxial rear

Connection Contact Type And Quantity:

3 receptacle, coaxial external

Special Features:

Threaded holes 2-56 unc-2b 0.086 in. Deep 4 places

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200