NSN 5895-01-106-2640

Reference Signal Generator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5895-01-106-2640



Overall Length: 8.350 inches **Overall Height:** 4.960 inches **Overall Width:** 8.000 inches **Vibration Resistance Range In Hertz:** +5.0/+33.0 **Individual Section Quantity: Vibration Resistance Amplitude:** 5.5 gravitational units **Shock Resistance Rating In Gravitational Units:** 60.0 **Operating Tempurature Range:** +0.0/+75.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 20-1242251-2-07397 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Installation Design:** Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 13.0 gigahertz 3rd output channel err-100 **Attenuation In Decibels:** 24.0 **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: Not rated **Overall Gain:** Not rated Impedance Rating Per Channel: 50.000 ohms input channel err-100

NSN 5895-01-106-2640

Reference Signal Generator - Page 2 of 2



Pulse Peak	Amplitude	Per	Channel:
------------	------------------	-----	----------

Not rated

Maximum Continuous Operating Time In Hours:

6800.0

Shock Pulse Duration Time:

20.0 milliseconds

Connection Type And Location:

Receptacle, coaxial bottom

Connection Contact Type And Quantity:

4 receptacle, coaxial external

External Dc Operating Voltage In Volts:

24.0 2nd voltage err-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200