50.000 ohms input channel err-100

Reference Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-106-2640

| Overall Length: | |
|---|--|
| 8.350 inches | |
| Overall Height: | |
| 4.960 inches | |
| Overall Width: | |
| 8.000 inches | |
| Vibration Resistance Range In Hertz: | |
| +5.0/+33.0 | |
| Individual Section Quantity: | |
| 3 | |
| Vibration Resistance Amplitude: | |
| 5.5 gravitational units | |
| Shock Resistance Rating In Gravitational Units: | |
| 60.0 | |
| Operating Tempurature Range: | |
| +0.0/+75.0 degrees celsius | |
| Average Life Measurement: | |
| Not rated | |
| Basic Shape Style: | |
| Rectangular or square | |
| Identification Designator: | |
| 20-1242251-2-07397 | |
| Maximum Operating Altitude Rating: | |
| Not rated | |
| Inclosure Type: | |
| Encased | |
| Installation Design: | |
| Mechanical | |
| Circuit Construction Type: | |
| Solid state | |
| Frequency Per Channel: | |
| 13.0 gigahertz 3rd output channel err-100 | |
| Attenuation In Decibels: | |
| 24.0 | |
| Average Power Rating Per Channel: | |
| Not rated | |
| Signal Voltage Rating Per Channel: | |
| Not rated | |
| Overall Gain: | |
| Not rated | |
| Impedance Rating Per Channel: | |
| | |

NSN 5895-01-106-2640

Reference Signal Generator - Page 2 of 2



Pulse Peak Amplitude Per Channel:Not ratedMaximum Continuous Operating Time In Hours:6800.0Shock Pulse Duration Time:20.0 millisecondsConnection Type And Location:Receptacle, coaxial bottomConnection Contact Type And Quantity:4 receptacle, coaxial externalExternal Dc Operating Voltage In Volts:24.0 2nd voltage err-100Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200