NSN 5895-01-117-2926

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-117-2926

Overall Length:

Between 0.480 inches and 0.500 inches

Overall Height:

Between 0.390 inches and 0.405 inches

Overall Width:

Between 0.210 inches and 0.230 inches

Vibration Resistance Range In Hertz:

+2.0/+2000.0

Vibration Resistance Amplitude:

20.0 gravitational units

Shock Resistance Rating In Gravitational Units:

100.0

Operating Tempurature Range:

-50.0/+100.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

Sam1-15542

Maximum Operating Altitude Rating:

656000.0 feet

Inclosure Type:

Hermetically sealed

Installation Design:

Module

Circuit Construction Type:

Solid state

Frequency Per Channel:

600.1 megahertz 3rd input channel err-100

Attenuation In Decibels:

3.5

Average Power Rating Per Channel:

50.0 milliwatts input

Overall Gain:

1.1 decibels

Impedance Rating Per Channel:

50.000 ohms 4th operating channel

Shock Pulse Duration Time:

6.0 microseconds

Connection Type And Location:

Printed circuit bottom

NSN 5895-01-117-2926

Frequency Mixer Stage - Page 2 of 2



		_		
Connection	Contact	Tyna	Δnd	Ouantity
2011116611011	Contact	IVDC	AII W	Qualitity.

8 printed circuit external

Special Features:

Emi shielded

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200