## NSN 5895-01-120-0959

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-120-0959
Overall Length:
0.780 inches
Overall Diameter:
0.375 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-56.0/+71.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Cylindrical
Maximum Operating Altitude Rating:
50000.000 feet
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Panel
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
85.0 megahertz operating channel err-100
Attenuation In Decibels:
1.5
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:

Not rated

Not rated

**Connection Type And Location:** 

**Maximum Continuous Operating Time In Hours:** 

Wire lead terminals bottom

## NSN 5895-01-120-0959

Frequency Mixer Stage - Page 2 of 2



~ · · · · · · · · · · · ·	<b>~</b>	-		<b>~</b>
Connection	Contact	IVpe	Ana	Quantity:

5 wire lead terminals external

**Precious Material And Location:** 

External surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200