NSN 5895-01-120-9322



Frequency Mixer Stage - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5895-01-120-9322 **Overall Length:** 0.625 inches **Overall Height:** 0.150 inches **Overall Width:** 0.625 inches **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** Md-139-21912 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state **Frequency Per Channel:** 1.0 megahertz input channel and 500.0 megahertz input channel **Attenuation In Decibels:** 9.0 **Average Power Rating Per Channel:** 400.0 milliwatts input **Signal Voltage Rating Per Channel:** Not rated **Overall Gain:** Not rated Impedance Rating Per Channel: 50.000 ohms input channel

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Wire lead terminals bottom and wire lead terminals top

NSN 5895-01-120-9322

Frequency Mixer Stage - Page 2 of 2



Connection Contact Type And Quantity:

8 wire lead terminals external

Precious Material And Location:

Internal surfaces gold and terminals gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200