NSN 5895-01-121-3768

Electronic Frequency Converter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5895-01-121-3768



Reliability Indicator: Not established **Overall Length:** Between 3.500 inches and 3.600 inches **Overall Height:** Between 0.650 inches and 0.670 inches Overall Width: Between 2.630 inches and 2.690 inches **Environmental Protection:** Fungus proof and salt spray resistant **Vibration Resistance Range In Hertz:** Not rated **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Average Life Rating:** 500000.0 **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Hours **Average Life Rating In Hours:** 500000.0 **End Application:** Pacer gym **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 80000.000 feet **Inclosure Type: Encased Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state

NSN 5895-01-121-3768

Electronic Frequency Converter - Page 2 of 2



Frequency Per Channel:
4.4 gigahertz operating channel err-100
Variation Frequency Rating In Decibels:
12.0
Attenuation In Decibels:
5.0
Average Power Rating Per Channel:
1.0 watts input
Signal Voltage Rating Per Channel:
15.000 volts input
Overall Gain:
0.1 volts
Impedance Rating Per Channel:
125.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
5000.0
Connection Type And Location:
Receptacle, coaxial left side
Connection Contact Type And Quantity:
1 receptacle, coaxial external
External Dc Operating Voltage In Volts:
15.0 single voltage
Fsc Application Data:
Radar altimeter
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

A32200