NSN 5895-01-123-6109



Frequency Mixer Stage - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5895-01-123-6109 **Overall Length:** 0.800 inches **Overall Height:** 0.400 inches **Overall Width:** 0.400 inches **Vibration Resistance Range In Hertz:** +2.0/+2000.0 **Vibration Resistance Amplitude:** 12.0 gravitational units **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** Sra-imgi-15542 **Maximum Operating Altitude Rating:** 656000.000 feet **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state 500.0 hertz operating channel and 2.0 gigahertz operating channel

Frequency Per Channel: **Attenuation In Decibels:** 8.5 **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** Not rated **Overall Gain:** Not rated Impedance Rating Per Channel: Not rated **Maximum Continuous Operating Time In Hours:** Not rated

NSN 5895-01-123-6109

Frequency Mixer Stage - Page 2 of 2



•	onnection	Type	And	Location:
•	OHIHECTIOH	IVDE	Allu	Location.

Printed circuit bottom

Connection Contact Type And Quantity:

8 printed circuit external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200