## NSN 5895-01-124-2604

Frequency Mixer Stage - Page 1 of 2

Overall Length: 0.515 inches Overall Height: 0.125 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5895-01-124-2604

0.390 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-54.0/+100.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
927323-2b-82577
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
700.0 megahertz input channel err-100
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
250.0 milliwatts input
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms input channel
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Wire lead terminals left side and wire lead terminals right side

## NSN 5895-01-124-2604

Frequency Mixer Stage - Page 2 of 2



Connection Contact Type And Quantity:
8 wire lead terminals external

**Precious Material And Location:** 

Terminals gold

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200