NSN 5895-01-129-0109

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-129-0109

Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
Not rated
Average Life Measurement:
Not rated
Basic Shape Style:
Irregular
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical
Circuit Construction Type:
Any acceptable
Frequency Per Channel:
0.0 megahertz output channel and 890.0 megahertz output channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
75.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, coaxial bottom and receptacle, coaxial left side and receptacle, coaxial right side
Connection Contact Type And Quantity:
3 receptacle, coaxial external
Criticality Code Justification:
Feat
Special Features:
Isolation 26 decibels

NSN 5895-01-129-0109

Frequency Mixer Stage - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200