## NSN 5895-01-129-0110

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-129-0110

View Online at https://aerobasegroup.com/nsn/5895-01-129-0110
Overall Length:
Between 0.480 inches and 0.500 inches
Overall Height:
Between 0.380 inches and 0.455 inches
Overall Width:
Between 0.210 inches and 0.230 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Shock Resistance Rating In Gravitational Units:
50.0
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
2770-51-301-0134
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
2.0 megahertz input channel and 500.0 megahertz input channel
Average Power Rating Per Channel:
100.0 milliwatts input
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
4 liters of liquid nitrogen drain
Criticality Code Justification:
Feat
Special Features:

**Special Features:** 

opeciai i catares.

Weapon systen essential

## NSN 5895-01-129-0110

Frequency Mixer Stage - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200