## NSN 5895-01-144-3481

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-144-3481

view Offilite at https://defobasegroup.com/hsi//5055-01-144-5401
Overall Length:
Between 0.770 inches and 0.800 inches
Overall Height:
Between 0.355 inches and 0.415 inches
Overall Width:
Between 0.370 inches and 0.400 inches
Operating Tempurature Range:
-65.0/+100.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encapsulated
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
5.0 megahertz operating channel and 500.0 megahertz operating channel
Frequency Adjustment Type:
Continuous
Average Power Rating Per Channel:
400.0 milliwatts input
Impedance Rating Per Channel:
50.000 ohms operating channel
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
8 pin external
Test Data Document:
81349-mil-m-28837 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:

**Fsc Application Data:** 

Miscellaneous communications equip.

81349-mil-m-28837/1 government specification

Shelf Life:

N/a

## NSN 5895-01-144-3481

Frequency Mixer Stage - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200