NSN 5895-01-153-7634

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-153-7634 **Overall Length:** 1.009 inches **Overall Height:** 0.150 inches **Overall Width:** 0.510 inches **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -40.0/+95.0 degrees celsius Average Life Rating: 20000.0 **Average Life Measurement: Average Life Rating In Hours:** 20000.0 **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 0.001 gigahertz output channel and 3.500 gigahertz output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 300.0 milliwatts input Signal Voltage Rating Per Channel: Not rated **Overall Gain:** Not rated Impedance Rating Per Channel:

Not rated

50.000 ohms operating channel

Maximum Continuous Operating Time In Hours:

NSN 5895-01-153-7634

Frequency Mixer Stage - Page 2 of 2



Wire lead terminals bottom and wire lead terminals top

Connection Contact Type And Quantity:

8 wire lead terminals external

Precious Material And Location:

Case and terminal surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200