## NSN 5895-01-153-7634

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-153-7634

| Overall Length:   |
|---|
| 1.009 inches  |
| Overall Height:   |
| 0.150 inches  |
| Overall Width:  |
| 0.510 inches  |
| Vibration Resistance Range In Hertz:                              |
| Not rated   |
| Shock Resistance Rating In Gravitational Units:                   |
| Not rated   |
| Operating Tempurature Range:                                      |
| -40.0/+95.0 degrees celsius                                       |
| Average Life Rating:  |
| 20000.0   |
| Average Life Measurement:   |
| Hours   |
| Average Life Rating In Hours:                                     |
| 20000.0   |
| Basic Shape Style:  |
| Rectangular or square   |
| Maximum Operating Altitude Rating:                                |
| Not rated   |
| Inclosure Type:   |
| Encased   |
| Installation Design:  |
| Module  |
| Circuit Construction Type:  |
| Solid state   |
| Frequency Per Channel:  |
| 0.001 gigahertz output channel and 3.500 gigahertz output channel |
| Attenuation In Decibels:  |
| Not rated   |
| Average Power Rating Per Channel:                                 |
| 300.0 milliwatts input  |
| Signal Voltage Rating Per Channel:                                |
| Not rated   |
| Overall Gain:   |
| Not rated   |
| Impedance Rating Per Channel:                                     |
| 50.000 ohms operating channel                                     |
| Maximum Continuous Operating Time In Hours:                       |
| Not rated   |
|   |

## NSN 5895-01-153-7634

Frequency Mixer Stage - Page 2 of 2



**Connection Type And Location:** Wire lead terminals bottom and wire lead terminals top **Connection Contact Type And Quantity:** 8 wire lead terminals external **Precious Material And Location:** Case and terminal surfaces gold **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A32200