

View Online at <https://aerobasegroup.com/nsn/5895-01-158-8728>

Overall Length:

Between 0.490 inches and 0.530 inches

Overall Height:

0.150 inches

Overall Width:

Between 0.365 inches and 0.405 inches

Environmental Protection:

Fungus proof and moisture proof and salt spray resistant and shock resistant and vibration

Operating Temperature Range:

-18.0/+85.0 degrees celsius

Average Life Measurement:

Indefinite

End Application:

Mixer stage frequency an/trc-170

Basic Shape Style:

Rectangular or square

Identification Designator:

954524-1-49956

Maximum Operating Altitude Rating:

10000.0 feet

Inclosure Type:

Encapsulated

Installation Design:

Panel

Circuit Construction Type:

Solid state

Frequency Per Channel:

500.0 kilohertz 2nd input channel err-100 and 500.0 megahertz 2nd input channel err-100

Average Power Rating Per Channel:

400.0 milliwatts output

Impedance Rating Per Channel:

50.000 ohms 2nd output channel err-100

Maximum Continuous Operating Time In Hours:

30000.0

Connection Type And Location:

Wire lead terminals left side and wire lead terminals right side

Connection Contact Type And Quantity:

8 wire lead terminals external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200