

View Online at <https://aerobasegroup.com/nsn/5895-01-158-8728>

**Overall Length:**

Between 0.490 inches and 0.530 inches

**Overall Height:**

0.150 inches

**Overall Width:**

Between 0.365 inches and 0.405 inches

**Environmental Protection:**

Fungus proof and moisture proof and salt spray resistant and shock resistant and vibration

**Operating Temperature Range:**

-18.0/+85.0 degrees celsius

**Average Life Measurement:**

Indefinite

**End Application:**

Mixer stage frequency an/trc-170

**Basic Shape Style:**

Rectangular or square

**Identification Designator:**

954524-1-49956

**Maximum Operating Altitude Rating:**

10000.0 feet

**Inclosure Type:**

Encapsulated

**Installation Design:**

Panel

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

500.0 kilohertz 2nd input channel err-100 and 500.0 megahertz 2nd input channel err-100

**Average Power Rating Per Channel:**

400.0 milliwatts output

**Impedance Rating Per Channel:**

50.000 ohms 2nd output channel err-100

**Maximum Continuous Operating Time In Hours:**

30000.0

**Connection Type And Location:**

Wire lead terminals left side and wire lead terminals right side

**Connection Contact Type And Quantity:**

8 wire lead terminals external

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32200