## NSN 5895-01-159-4274

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-159-4274

Overall Length:
0.520 inches
Overall Height:
0.420 inches
Overall Width:
0.520 inches
Environmental Protection:
Shock resistant
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Average Life Measurement:
Indefinite
End Application:
Countermeasures receiving set an/urq-3
Basic Shape Style:
Rectangular or square
Identification Designator:
723112-10-05869
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Decision.
Installation Design:
Module
_
Module
Module Circuit Construction Type:
Module  Circuit Construction Type:  Solid state
Module  Circuit Construction Type:  Solid state  Average Power Rating Per Channel:
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel:
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location:
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom Connection Contact Type And Quantity:
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom Connection Contact Type And Quantity: 3 wire lead terminals external
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom Connection Contact Type And Quantity: 3 wire lead terminals external Precious Material:
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom  Connection Contact Type And Quantity: 3 wire lead terminals external  Precious Material: Gold
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom Connection Contact Type And Quantity: 3 wire lead terminals external Precious Material: Gold Shelf Life:
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom Connection Contact Type And Quantity: 3 wire lead terminals external Precious Material: Gold Shelf Life: N/a
Module  Circuit Construction Type: Solid state  Average Power Rating Per Channel: 300.0 milliwatts input Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Wire lead terminals bottom Connection Contact Type And Quantity: 3 wire lead terminals external Precious Material: Gold Shelf Life: N/a

## NSN 5895-01-159-4274

Frequency Mixer Stage - Page 2 of 2



Fiig:

A32200