## NSN 5895-01-160-4222



Frequency Mixer Stage - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5895-01-160-4222 **Overall Length:** 1.050 inches **Overall Height:** 0.525 inches Overall Width: Between 0.500 inches and 0.525 inches **Operating Tempurature Range:** -54.0/+100.0 degrees celsius Average Life Rating: 100000.0 **Average Life Measurement:** Hours Average Life Rating In Hours: 100000.0 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Circuit Construction Type:** Any acceptable Frequency Per Channel: 0.5 megahertz operating channel and 500.0 megahertz operating channel **Frequency Adjustment Type:** Continuous **Average Power Rating Per Channel:** 140.0 milliwatts input **Connection Type And Location:** Wire lead terminals bottom **Connection Contact Type And Quantity:** 6 wire lead terminals external **Test Data Document:** 81349-mil-m-28837 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:** 

Yes - demil/mli

**Demilitarization:** 

## NSN 5895-01-160-4222

Frequency Mixer Stage - Page 2 of 2



Fiig:

A32200