Radio Frequency Detector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-163-7493

## **Overall Length:** Between 1.500 inches and 1.600 inches **Overall Diameter:** Between 0.370 inches and 0.491 inches **Environmental Protection:** Moisture proof and salt spray resistant and shock resistant Vibration Resistance Range In Hertz: +10.0/+55.0 **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 50.0 **Operating Tempurature Range:** -65.0/+100.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Cylindrical **Maximum Operating Altitude Rating:** 15000.0 feet **Inclosure Type:** Encapsulated **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state **Frequency Per Channel:** 10.0 megahertz operating channel and 4.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Connector, plug left side and receptacle, coaxial right side **Connection Contact Type And Quantity:** 1 connector, plug external and 1 receptacle, coaxial external Shelf Life:

N/a

## NSN 5895-01-163-7493

Radio Frequency Detector - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200