

View Online at <https://aerobasegroup.com/nsn/5895-01-164-8733>

Overall Length:

0.415 inches

Overall Diameter:

Between 0.335 inches and 0.370 inches

Vibration Resistance Range In Hertz:

Not rated

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

-54.0/+100.0 degrees celsius

Average Life Rating:

100000.0

Average Life Measurement:

Hours

Average Life Rating In Hours:

100000.0

End Application:

An/usm-464 test set, countermeasures

Basic Shape Style:

Cylindrical

Inclosure Type:

Encapsulated

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Electron tube

Frequency Per Channel:

0.4 hertz operating channel and 500.0 gigahertz operating channel

Frequency Adjustment Type:

Continuous

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Wire lead terminals bottom

Connection Contact Type And Quantity:

4 wire lead terminals external

Test Data Document:

81349-mil-m-28837 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200