

View Online at <https://aerobasegroup.com/nsn/5895-01-165-6621>

**Overall Length:**

Between 0.480 inches and 0.500 inches

**Overall Height:**

Between 0.550 inches and 0.605 inches

**Overall Width:**

Between 0.210 inches and 0.230 inches

**Environmental Protection:**

Moisture proof and shock resistant and vibration

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Vibration Resistance Amplitude:**

10.0 gravitational units

**Shock Resistance Rating In Gravitational Units:**

50.0

**Operating Temperature Range:**

-57.0/+100.0 degrees celsius

**Average Life Measurement:**

Not rated

**Basic Shape Style:**

Rectangular or square

**Maximum Operating Altitude Rating:**

15000.0 feet

**Inclosure Type:**

Encapsulated

**Operating Control Method:**

Automatic

**Installation Design:**

Module

**Control Type:**

Remote

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

1.0 hertz operating channel and 1000.0 megahertz operating channel

**Average Power Rating Per Channel:**

50.0 milliwatts input

**Impedance Rating Per Channel:**

50.000 ohms operating channel

**Shock Pulse Duration Time:**

11.0 milliseconds

**Connection Type And Location:**

Err-060 glad hand quick disconnect

**Connection Contact Type And Quantity:**

8 liters of liquid nitrogen drain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32200