

View Online at <https://aerobasegroup.com/nsn/5895-01-165-6621>

Overall Length:

Between 0.480 inches and 0.500 inches

Overall Height:

Between 0.550 inches and 0.605 inches

Overall Width:

Between 0.210 inches and 0.230 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+10.0/+55.0

Vibration Resistance Amplitude:

10.0 gravitational units

Shock Resistance Rating In Gravitational Units:

50.0

Operating Temperature Range:

-57.0/+100.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

15000.0 feet

Inclosure Type:

Encapsulated

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

1.0 hertz operating channel and 1000.0 megahertz operating channel

Average Power Rating Per Channel:

50.0 milliwatts input

Impedance Rating Per Channel:

50.000 ohms operating channel

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Err-060 glad hand quick disconnect

Connection Contact Type And Quantity:

8 liters of liquid nitrogen drain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200