NSN 5895-01-179-1742

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-179-1742

Inclosure Material:
Aluminum
Overall Length:
0.900 inches
Overall Height:
0.550 inches
Overall Width:
0.900 inches
Environmental Protection:
Fungus proof and moisture proof and shock resistant and vibration
Operating Tempurature Range:
-46.0/+85.0 degrees celsius
Storage Tempurature Range:
-62.0/+85.0 degrees celsius
Average Life Measurement:
Hours
End Application:
Radar data transfer subsystem, an/gpn-2 (v) 1
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
10000.0 feet
Inclosure Type:
Encased
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
10.0 megahertz operating channel and 1.5 gigahertz operating channel
Average Power Rating Per Channel:
200.0 watts input
Impedance Rating Per Channel:
50.000 ohms operating channel
Connection Type And Location:
Receptacle, coaxial front and receptacle, coaxial left side and receptacle, coaxial right side
Connection Contact Type And Quantity:
3 receptacle, coaxial external
Supplementary Features:
Case matl: aluminum alloy, qq-a-225/8, 6061-t6; finish: gold plate iaw mil-g-45204, type iii, grade a, class 1 over chemical conversion
coating iaw mil-c-5541, class 3, or nickel plate iaw qq-n-290, class i, grade f
Shelf Life:

NSN 5895-01-179-1742

Frequency Mixer Stage - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200