NSN 5895-01-246-1003

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-246-1003 **Inclosure Material:** Aluminum **Overall Length:** 1.630 inches **Overall Height:** 2.010 inches **Overall Width:** 0.660 inches **Environmental Protection:** Shock resistant and vibration Vibration Resistance Range In Hertz: +4.0/+15.0 and +16.0/+25.0 and +26.0/+33.0 **Vibration Resistance Amplitude:** 0.15 inches total excursion and 0.1 inches total excursion and 0.05 inches total excursion **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** +0.0/+65.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 40000.0 feet **Inclosure Type:** Encased Installation Design: Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 2.0 gigahertz output channel and 4.0 gigahertz output channel **Shock Pulse Duration Time:** 6.0 milliseconds **Connection Type And Location:** Receptacle, coaxial bottom and receptacle, coaxial left side and receptacle, coaxial top **Connection Contact Type And Quantity:** 3 receptacle, coaxial external Shelf Life: N/a **Unit Of Measure:**

--

NSN 5895-01-246-1003

Frequency Mixer Stage - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200