NSN 5895-01-247-8998

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-247-8998

view Offilite at https://aerobasegroup.com/hsi//3033-01-247-0330
Overall Length:
Between 0.480 inches and 0.500 inches
Overall Height:
Between 0.170 inches and 0.255 inches
Overall Width:
Between 0.210 inches and 0.230 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Vibration Resistance Range In Hertz:
+2.0/+2000.0
Vibration Resistance Amplitude:
20.0 gravitational units
Shock Resistance Rating In Gravitational Units:
100.0
Operating Tempurature Range:
-54.0/+100.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
Tfm2-5-15542
Maximum Operating Altitude Rating:
656000.0 feet
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
1.0 megahertz output channel and 1000.0 megahertz output channe
Shock Pulse Duration Time:
6.0 milliseconds
Connection Type And Location:
Err-060 glad hand quick disconnect

4 liters of liquid nitrogen drain

Connection Contact Type And Quantity:

NSN 5895-01-247-8998

Frequency Mixer Stage - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200