

View Online at <https://aerobasegroup.com/nsn/5895-01-248-7292>

Overall Length:

20.125 inches

Overall Height:

10.500 inches

Overall Width:

8.500 inches

Basic Shape Style:

Rectangular or square

Installation Design:

Rack

Circuit Construction Type:

Solid state

Frequency Per Channel:

1.000 megahertz 1st input channel and 1.544 megahertz 2nd input channel and 5.000 megahertz 3rd input channel

Frequency Adjustment Type:

Stepped

Individual Step Frequency:

8.0 kilohertz

Impedance Rating Per Channel:

100.000 ohms 1st output channel err-100

Operating Ac Frequency In Hertz:

50.0 single voltage and 60.0 single voltage

External Dc Operating Voltage In Volts:

48.0 2nd voltage err-100

External Ac Operating Voltage In Volts:

220.0 2nd voltage

Phase:

Single

Special Features:

Xexternal input capability is changableby plug-in modules; clock amplifier section has of 72 outputs strappable, making outputs either balanced or unbalanced; visible and audible alarm indicates failure of any major component

Functional Description:

Operates from square or sinusoidal external reference signals, 1 vrms; accepts 3 independent reference inputs (1.0, 1.544 or 5.0 mhz) and operates 1; 12 output cards each drive 6 output lines terminating in 100 ohms; low rate driver cards provide 27 selectable frequencies from 75 hz to 512 khz; high rate driver cards provide4 selectable frequencies: 2 fixed (1.536 & 5.000 mhz) and 2 programmable in 8 khz steps from 1 mhz to 13.336 mhz

Supplementary Features:

Lock distribution

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig: