

View Online at <https://aerobasegroup.com/nsn/5895-01-278-5939>

**Case Material:**

Aluminum alloy

**Maximum Voltage Rating In Volts:**

6.0 ac

**End Application:**

B1b receiver transmitter

**Inclosure Type:**

Encased

**Current Rating In Amps:**

1.0

**Terminal Location:**

Back

**Power Source:**

External

**Terminal Type And Quantity:**

1 quick disconnect, male

**Maximumlength:**

5.750 inches

**Maximumwidth:**

5.000 inches

**Maximumheight:**

3.300 inches

**Criticality Code Justification:**

Feat

**Phase:**

Single

**Special Features:**

Electrostatic discharge sensitive

**Functional Description:**

Provides the operator operational access to the remotely connected receiving set, radio crc-85-461; provides operator capability to turn on the set, initiate a mission configuration, receive indications of incoming messages, set operational status, and zeroize the set cryptographic variables

**Supplementary Features:**

C/o set on/off switch, mission profile selection switch, cryptographic variable zeroize (cvz) switch, receive mode selection switch, print format selection switch, set self-test switch, lamp test switch, message indicator, message indicator clear switch, set go and fault indicators, manual fault summary printout switch, manual override switch for frequency scanning; mounted by 4 deutsch fasteners on 2.750 in. X 5.188 in. Mtg centers

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A31700