## NSN 5895-01-295-2714

Multiplexer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5895-01-295-2714

Overall Length: 7.800 inches Overall Height: 0.600 inches Overall Width: 6.900 inches End Application: Digital multiplexer-demultiplexerdmx-a3/c3 Input Impedance Rating: 120.0 ohms Output Impedance Rating: 120.0 ohms Supplementary Features: Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-a transmit data inputs; generates overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipme state; etched-circuit module that fits an 8.75 in card cage; input/output signals connect via a 72-pin edge-on connector	
Overall Height: 0.600 inches Overall Width: 6.900 inches End Application: Digital multiplexer-demultiplexerdmx-a3/c3 Input Impedance Rating: 120.0 ohms Output Impedance Rating: 120.0 ohms Supplementary Features: Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipment	
Overall Width: 6.900 inches  End Application: Digital multiplexer-demultiplexerdmx-a3/c3 Input Impedance Rating: 120.0 ohms  Output Impedance Rating: 120.0 ohms  Supplementary Features: Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generates overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipment of the stream of the sync of test equipment of test equipment of the sync of test equipment of test equipment of tes	
Overall Width: 6.900 inches  End Application: Digital multiplexer-demultiplexerdmx-a3/c3 Input Impedance Rating: 120.0 ohms  Output Impedance Rating: 120.0 ohms  Supplementary Features: Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generates overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipment and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipment and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipment.	
6.900 inches  End Application:  Digital multiplexer-demultiplexerdmx-a3/c3  Input Impedance Rating:  120.0 ohms  Output Impedance Rating:  120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipment of the stream of the sync of test equipment of the sync of test eq	
End Application:  Digital multiplexer-demultiplexerdmx-a3/c3  Input Impedance Rating:  120.0 ohms  Output Impedance Rating:  120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
Digital multiplexer-demultiplexerdmx-a3/c3  Input Impedance Rating:  120.0 ohms  Output Impedance Rating:  120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
Input Impedance Rating:  120.0 ohms  Output Impedance Rating:  120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
120.0 ohms  Output Impedance Rating:  120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generates overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
Output Impedance Rating:  120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generates overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
120.0 ohms  Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
Supplementary Features:  Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
Ds-3 transmit framing forms the ds-3 streams from the gated ds-b transmit data and the gated ds-3 transmit data inputs; generated overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
overhead and periodic stuff bits and routes data to ds-3 interface; gated ds-b and gated ds-e clocks are generated and forwarded multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipments.	
multiplexers; power reqd -5.2 vdc; red led indicates externally excited module failure; test points provded for sync of test equipme	i
	o external
state; etched-circuit module that fits an 8.75 in card cage; input/output signals connect via a 72-pin edge-on connector	nt; solid
Fsc Application Data:	
Ds-3tx framing	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
T187-f	