Electronic Frequency Converter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5895-01-298-2130

Overall Height:

1.130 inches

Vibration Resistance Range In Hertz:

+4.0/+33.0 and +34.0/+50.0

Vibration Resistance Amplitude:

0.08 inches total excursion and 0.03 inches total excursion

Operating Tempurature Range:

-28.0/+90.0 degrees celsius

Average Life Rating:

50000.0

Average Life Measurement:

Hours

Average Life Rating In Hours:

50000.0

End Application:

An/usc-3 (v) satcom terminals

Basic Shape Style:

Irregular

Maximum Operating Altitude Rating:

10000.0 feet

Operating Control Method:

Automatic

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

20.2 gigahertz 2nd input channel err-100 and 21.2 gigahertz 2nd input channel err-100

Connection Type And Location:

Pin front and receptacle, coaxial front

Connection Contact Type And Quantity:

3 pin external and 2 receptacle, coaxial internal

External Dc Operating Voltage In Volts:

12.0 single voltage and 15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200