NSN 5895-01-305-6302



Frequency Mixer Stage - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5895-01-305-6302 **Overall Length:** 0.800 inches **Overall Height:** 0.590 inches **Overall Width:** 0.400 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Shock Resistance Rating In Gravitational Units:** 50.0 **Operating Tempurature Range:** -55.0/+100.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 5820-01-237-3800 transmitter, radio **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 70000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic **Installation Design:** Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 0.0 megahertz operating channel and 500.0 megahertz operating channel **Average Power Rating Per Channel:** 500.0 milliwatts input **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:**

Shelf Life:

N/a

8 pin external

NSN 5895-01-305-6302

Frequency Mixer Stage - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200