Radio Frequency Detector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-354-9874

Overall Length:
1.620 inches
Overall Diameter:
0.380 inches
Vibration Resistance Range In Hertz:
+80.0/+200.0
Vibration Resistance Amplitude:
20.0 gravitational units
Shock Resistance Rating In Gravitational Units:
500.0
Operating Tempurature Range:
-65.0/+100.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Radar set an/tpt-x
Basic Shape Style:
Cylindrical
Maximum Operating Altitude Rating:
50000.0 feet
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
0.01 gigahertz operating channel and 33.0 gigahertz operating channel
Average Power Rating Per Channel:
200.0 milliwatts input
Shock Pulse Duration Time:
0.5 milliseconds
Connection Type And Location:
Receptacle, coaxial left side and receptacle, coaxial right side
Connection Contact Type And Quantity:
2 receptacle, coaxial external
Shelf Life:
N/a

NSN 5895-01-354-9874

Radio Frequency Detector - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200