## NSN 5895-01-359-2040

Radio Frequency Detector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-359-2040

#### **Overall Length:**

Between 1.140 inches and 1.180 inches

#### **Overall Diameter:**

Between 0.300 inches and 0.325 inches

## Shock Resistance Rating In Gravitational Units:

100.0

#### **Operating Tempurature Range:**

+0.0/+65.0 degrees celsius

#### Average Life Measurement:

Not rated

End Application:

Receiver r-2299/sps-48

#### **Basic Shape Style:**

Cylindrical

Inclosure Type:

Encased

## **Operating Control Method:**

Automatic

## Installation Design:

Mechanical

### **Control Type:**

Remote

#### **Circuit Construction Type:**

Solid state

#### **Frequency Per Channel:**

2.0 gigahertz operating channel and 8.0 gigahertz operating channel

#### Signal Voltage Rating Per Channel:

125.000 millivolts output

### Shock Pulse Duration Time:

6.0 milliseconds

#### **Connection Type And Location:**

Receptacle, coaxial left side and receptacle, coaxial right side

#### **Connection Contact Type And Quantity:**

2 receptacle, coaxial external

#### **Precious Material And Location:**

Body and connector surfaces gold

### **Precious Material:**

Gold

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5895-01-359-2040

Radio Frequency Detector - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A32200

